

Laminated plate of less heat expansion index - comprising laminating base plate obtd. by sintering sheet material of glass fibre with ceramic powder contained binder, with sheet of prepreg

Patent Assignee: SHIN KOBE ELECTRIC MACHINERY (KOBE )

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 6305078	A	19941101	JP 9399921	A	19930427	199503 B

Priority Applications (No Type Date): JP 9399921 A 19930427

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 6305078	A		3	B32B-018/00	

Abstract (Basic): JP 6305078 A

Mfr. comprises laminating a base plate obtd. by coating and sintering a sheet material of a glass fibre with a ceramic powder contg. an organic binder, with at least one sheet of prepreg obtd. by immersing a sheet of base material with a thermosetting resin and heat-pressing to form a laminate plate. The ceramic powder used includes zirconia, alumina, cordierite, spinel and crystobirite.

The organic binder includes an organic solvent-soluble binder e.g. polyvinyl butyral, cellulose acetate, cellulose acetate butylate and water-soluble binder e.g. polyvinyl alcohol, methyl cellulose and acrylic polymer. The base glass fibre sheet is mfd. from 200-400 yarns of a glass fibre yarn of 5-9 microns in diameter. The thermosetting resin used includes epoxy resin and phenolic resin e.g. a novlak resin.

USE/ADVANTAGE - The laminated sheet is composed of a ceramic plate and a thermosetting resin layer and has less heat expansion index and is capable of being processed mechanically.

Dwg.0/0

Title Terms: LAMINATE; PLATE; LESS; HEAT; EXPAND; INDEX; COMPRISE; LAMINATE ; BASE; PLATE; OBTAIN; SINTER; SHEET; MATERIAL; GLASS; FIBRE; CERAMIC; POWDER; CONTAIN; BIND; SHEET; PREPREG

Derwent Class: A18; A21; A32; L02; P73

International Patent Class (Main): B32B-018/00

International Patent Class (Additional): B29C-043/18; B29K-105-06;

B32B-017/04; B32B-031/12

File Segment: CPI; EngPI

?